

Hose Reel 886 Ex

ATEX approved stainless steel hose reel when corrosive resistance is required.



The Nederman stainless steel hose reel 886 Ex is a robust hose reel with large hose capacity for heavy duty industrial use. This hose reel is constructed for environments where high hygiene and corrosion resistance is required.

886 EX hose reel in stainless steel is approved for use in zones 1, 2, 21 and 22 in accordance with ATEX 2014/34/EC, Equipment group II, Category 2G D.

- Unique design makes easy cleaning
- Up to 25 m (82 ft.) hose capacity
- Meets international hygienic requirement
- ATEX approved

Product name	Hose Reel 886 Ex
Connection hose length (m)	-
Type of hose	M
Colour	Stainless
Diameter, connection hose (mm)	19





















Hose Reel 886 Ex

Media	Delivered with hose	Distribution hose length (m)	Max working pressure (Mpa)	Distribution hose diameter (mm)	Weight (kg)	Max hose length	Model
Compressed air ,Water	Yes	25	2	12.5	31		30804686
Compressed air ,Water	Yes	15	2	19	31		30804886
Compressed air ,Water	No		1,5	10	28	18	32800186
Water high pressure	No		25	12.5	28	25	32801386
Compressed air ,Water	No		10	12.5	31	25	30804786
Compressed air ,Water	No		7,5	19	31	20	30804986

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
M	Cover in CR and inner tube in NBR. Synthetic textile braid. Electrically conductive	-30 - 80	Female 60° cone, stainless steel	Female 60° cone, stainless steel	Male 60° cone	Male 60° cone

Hose Reel 886 Ex

	Accessory	Part No
	Roller guide.	30341550
	Pivoting bracket.	30372407
	Pivoting bracket ss.	30372408
	Water gun in chromium plated brass	30400110
	Water gun in stainless steel	30400210
	High temperature water gun	30400310
	Air gun, standard.	30410110
	Pivoting Wall bracket FZB	30373667
	Pivoting Wall bracket RF	30373668
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl. 1/2(m)-3/8(f) brass	30431510
	Swivl.coupl. 1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl. 1/2(m)-3/4(f) SS	30432010
	Watergun EX	30400211

Hose Reel 886 Ex

